

AIRS, AMSU-A, and Aqua Spacecraft Hardware Status

AIRS Level 1 Software Status

Denis Elliott

March 22, 2016

Copyright 2016
California Institute of Technology
Government sponsorship acknowledged



AIRS Status




AIRS Operational Status

- AIRS is in excellent health
- All available engineering parameter plots versus time are either flat or changing extremely slowly—no concerns
- Cooler A status remains unchanged since the anomaly of March 2014
 - Cooler does not update engineering telemetry or respond to commands
 - Compressor is running and focal plane temperature is as desired
 - Science data quality remains excellent




Number of AIRS channels with NE Δ T < 1K





AIRS Chopper Drive Current


March 22-24 2016 Pasadena CA



5




AIRS Scan Mirror Temperature






AIRS Choke Point Heater Current






AIRS Cooler B Drive Level





AIRS Focal Plane Temperature





AMSU-A Status




AMSU-A Operational Status

- AMSU-A mechanical parts and most of the electronics are in good health
- All engineering parameter trends are slow
- The A1-1 and A1-2 scanner currents are rising, but very slowly and are not alarming
- 8 of the 15 channels are perfectly healthy with no noise increase at all, but
 - Channel 4 failed in 2007 (declared non-operational on October 1 2007)
 - Channel 5 is now too noisy to contribute to Level 2
 - Channel 7 noise has exceeded specs since launch and has never been used for L2
 - Channel 6 noise has been increasing slowly since 2008, but is still a good channel
 - Channel 9 experienced occasional small bursts of noise early in the mission and is now experiencing them again, but it is still good
 - Channel 1 began experiencing increased noise in January 2012, seemed to recover, but its noise jumped up some in mid-2015—it is still good
 - Channel 2 also began experiencing increased noise in early 2012—its changes are even slower than Channel 1—it is still good




AMSU-A1-1 RF Shelf Temperature



Copyright 2016
California Institute of Technology
Government sponsorship acknowledged



AMSU-A2 RF Shelf Temperature




Copyright 2016
California Institute of Technology
Government sponsorship acknowledged



AMSU-A1-2 Noisy Bus Current


March 22-24 2016 Pasadena CA



14




AMSU-A Channel 6 ΝΕΔΤ



Copyright 2016
California Institute of Technology
Government sponsorship acknowledged




AMSU-A Channel 9 ΝΕΔΤ



Copyright 2016
California Institute of Technology
Government sponsorship acknowledged




AMSU-A Channel 1 ΝΕΔΤ



17



AMSU-A Channel 2 ΝΕΔΤ



Copyright 2016
California Institute of Technology
Government sponsorship acknowledged



Aqua Status And Anomalies

Copyright 2016
California Institute of Technology
Government sponsorship acknowledged



Aqua Spacecraft Health Status

- Aqua is in very good health
- Several anomalies have occurred over the years, but none have impacted operations yet
 - Solar array
 - Potentiometers used for orientation are noisy
 - Thermistor failure on one panel
 - Solar cell arrays
 - have lost 13 strings of solar cells (out of 132 on the spacecraft)
 - there is no impact to mission operations at this time
 - FMU/SSR hardware timeouts
 - Battery
 - Pressure too high early in mission but now in control
 - Power from one cell behaved erratically for several years but now seems OK
 - · Temperature of one cell was high for part of a day
 - Computer memory bit errors




Aqua Fuel Supply

- Occasional drag make up burns use only a very small amount of fuel
- Most fuel usage takes place in orbital inclination adjustment maneuvers, needed to keep Aqua properly aligned with other A-train instruments and to tightly control our 1:30 pm crossing time
 - Three or four such maneuvers are planned every year, near the vernal equinox
 - The most recent estimate of future fuel usage indicates that the hydrazine should last at least until 2021, and possibly longer
 - The plot on the next page was made before the Spring 2015 inclination adjustments, but it is the most recent available



Projected Aqua Fuel Usage





AMSR-E status

- Antenna anomaly forced turning off AMSR-E in October 2011
- Instrument powered back on (but antenna not restarted) in February 2012
- In December 2012 the antenna was restarted, but spinning at only 2 rpm (nominal was 40 rpm)
- The instrument was permanently powered off on February 3, 2016



Level 1 Software Courtesy of Evan Manning and George Aumann



Level 1B

- No major changes affecting radiances are envisioned
- Improvements in some L1B parameters are planned
 - Non-gaussian noise
 - C_{ij} flag
 - "Do not use for L2"
- The SRF frequencies in the output file remain the nominal ones
 - True frequencies are in a table
 - The differences are less than 1% of the SRF width—
 ignoring the shift results in a brightness temperature error
 of less than 0.1 K except on the sides of lines



Level 1C

- First version is available—does cleaning and gap filling well
 - At the GES DISC they maintain a rolling 1-month of products
 - At JPL we have a complete record from April 21, 2015 to present
- This version needs improvement handling the C_{ii} correction
 - Possible improvements are being tested
- Resampling radiances to a fixed frequency grid is planned for the next release—the algorithm is under development



Non-periodic spectral shift for whole mission From Larrabee Strow

- The overall shift is very small
- The existing exponential decay model remains good for continued use
- Short period
 effects (such as
 orbital) are not
 shown—they are
 on the same order
 or smaller than
 the seasonal shift




Figure 1: Relative variation in module M3 from clear-ocean spectra compared to output of get_yoff.m



Level 1D

- Major new development
- Intended to align AIRS and CrIS SRF and spectral sample positions by degrading both to the lowest common denominator
- Still in the conceptual stage
- This may work better with CrlS Full Resolution mode data